SDS 0224

```
Section 1 -- PRODUCT AND COMPANY IDENTIFICATION
______
                                                      HMIS CODES
                                                   Health
Flammability
Reactivity
PRODUCT NAME
  Renewz
                                                                  1
PRODUCT CODES
                                                   PPI
  82644, 82646, 82650
CHEMICAL FAMILY
  Inorganic Base
USE
  Condenser Coil Cleaner
                                         EMERGENCY TELEPHONE NO.
MANUFACTURER'S NAME
  The RectorSeal Corporation
                                          Chemtrec 24 Hours
  2601 Spenwick Drive
                                          (800)424-9300 USA
  Houston, Texas 77055 USA
                                          (703)527-3887 International
DATE OF VALIDATION
                                         TECHNICAL SERVICE TELEPHONE NO.
                                          (800)231-3345 or (713)263-8001
  January 23, 2015
DATE OF PREPARATION
  July 25, 2012
         Section 2 -- HAZARDS IDENTIFICATION
EMERGENCY OVERVIEW
OSHA Hazards
Corrosive
GHS CLASSIFICATION
Skin corrosion (Category 1A)
Serious eye damage (Category 1)
Acute aquatic toxicity (Category 3)
______
GHS Label elements, including precautionary statements
Pictogram: Corrosive
Signal Word: Danger
Hazard statement(s)
H314 - Causes severe skin burns and eye damage.
H402 - Harmful to aquatic life.
Precautionary statement(s)
P280 - Wear protective gloves/ protective clothing/ eye protection/ face protection.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor/ physician.
______
SUMMARY OF ACUTE HAZARDS
  Exposure to human tissue will result in irritation and chemical burns.
ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS
INHALATION
  Extremely corrosive to respiratory system.
EYE CONTACT
  Corrosive, contact causes severe eye burns.
SKIN CONTACT
  Corrosive to skin.
INGESTION
  Poison! Swallowing large quantities can cause death and burns to digestive
system.
SUMMARY OF CHRONIC HAZARDS
     Exposure to human tissue will result in irritation and chemical burns.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
 Individuals with pre-existing or chronic diseases of the eyes, skin
```

or persons with chemical sensitivity may have increased susceptibility to excessive exposures.

\_\_\_\_\_

### Section 3 -- COMPOSITION/INFORMATION ON INGREDIENTS

\_\_\_\_\_

INGREDIENT: Sodium Hydroxide PERCENTAGE BY WEIGHT: 15 CAS NUMBER: 1310-73-2 EC# : 215-185-5

\_\_\_\_\_\_

INGREDIENT: Potassium Silicate

PERCENTAGE BY WEIGHT: 2 CAS NUMBER: 1312-76-1

EC# : 215-199-1

\_\_\_\_\_\_

## Section 4 -- FIRST AID MEASURES

-----

If INHALED: If overcome by exposure, remove victim to fresh air

immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action

is essential.

If on SKIN: Flush with large amounts of water. If irritation or burns

occur, seek immediate medical attention.

If in EYES: Flush with large amounts of water for at least 15 minutes.

Get medical attention if irritation persists.

If SWALLOWED: If swallowed, call a physician immediately. Only induce

vomiting at the instruction of a physician. Never give

anything by mouth to an unconscious person.

\_\_\_\_\_\_

### Section 5 -- FIRE FIGHTING MEASURES

\_\_\_\_\_

## EXTINGUSING MEDIA

Use agents suitable for surrounding fires.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus (SCBA) and other protective clothing. Hazardous decomposition products possible (see Section 10). Dike area as run-off may create additional environmental contamination

UNUSUAL FIRE AND EXPLOSION HAZARDS: Decomposition forms toxic fumes of sodium oxide. Flammable gas may be produced on contact with metals.

\_\_\_\_\_\_

## Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep people away.

Wear chemical protective clothing. Stop discharge if possible. Isolate and remove discharged material. Flush and clean area with water

\_\_\_\_\_\_

# Section 7 -- HANDLING AND STORAGE

-----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed and upright when not in use. Store only in polyethylene or glass containers. DO NOT USE METAL CONTAINERS.

OTHER PRECAUTIONS: Do not permit workers to handle Renewz without proper training or proper protective equipment. Store in well-sealed containers, which are protected from physical damage. Empty containers may contain residues and vapors; treat as if full and observe all product precautions. Do not reuse container. KEEP OUT OF REACH OF CHILDREN.

\_\_\_\_\_\_

## Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

\_\_\_\_\_

INGREDIENT UNITS

Sodium Hydroxide

ACGIH TLV CL 2 mg/m3 OSHA PEL CL 2 mg/m3

\_\_\_\_\_

```
ACGIH TLV N/D OSHA PEL N/D
```

\_\_\_\_\_\_

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined, poorly ventilated areas, use NIOSH/MSHA approved self-contained breathing apparatus. None required for normal use in adequately ventilated areas where TLV is not exceeded.

VENTILATION - LOCAL EXHAUST: Acceptable

SPECIAL: Explosion proof

MECHANICAL (GENERAL): Preferable

OTHER: N/A

PROTECTIVE GLOVES: Rubber or neoprene

EYE PROTECTION: Chemical splash goggles (ANSI Z-87.1 or equivalent)

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended.

WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area.

Launder contaminated clothing before reuse.

## Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: >212 F (>100 C) @ 760mm Hg

SPECIFIC GRAVITY (H20 = 1): 1.2

VAPOR PRESSURE (mm Hg): 1 @ 77 F (20 C)

MELTING POINT: N/A
VAPOR DENSITY (AIR = 1): >1
EVAPORATION RATE (ETHYL ACETATE = 1): <1

APPEARANCE/ODOR: Clear Yellow Liquid/ Little or No Odor

SOLUBILITY IN WATER:

FLASH POINT:

LOWER EXPLOSION LIMIT:

UPPER EXPLOSION LIMIT:

N/D

N/D

N/D

VOLATILE ORGANIC COMPOUNDS(VOC)Content

(Theoretical Percentage By Weight): 0% or (0 g/L)

\_\_\_\_\_\_

### Section 10 -- STABILITY AND REACTIVITY

-----

STABILITY: Stable

CONDITIONS TO AVOID: Heat, sparks, open flames.

INCOMPATIBILITY (MATERIALS TO AVOID): Acids, flammable liquids, organics, halogens, metals, nitromethane. When wet, attacks chemically active metals such as aluminum, tin, lead, and zinc to produce flammable hydrogen gas.

HAZARDOUS DECOMPOSITION PRODUCTS: Decomposition forms toxic fumes of sodium oxide.

HAZARDOUS POLYMERIZATION: Will not occur.

\_\_\_\_\_\_

Section 11 -- TOXICOLOGY INFORMATION

-----

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

\_\_\_\_\_\_

TOXICOLOGY DATA Ingredient Name

\_\_\_\_\_

Sodium Hydroxide

Oral-Rabbit, adult LDLo:500 mg/kg

Inhalation-Rat LC50: N/D

Potassium Silicate

Oral-Rabbit, adult LD50: N/D Inhalation-Rat LC50: N/D

\_\_\_\_\_\_

Section 12 -- Ecological Information

\_\_\_\_\_\_

ECOLOGICAL DATA

Ingredient Name

-----

Food Chain Concentration Potential None WATERFOWL TOXICITY N/D None AOUATIC TOXICITY 125 ppm/96 hr/mosquito fish/TLm Potassium Silicate Food Chain Concentration Potential N/D WATERFOWL TOXICITY N/D BOD N/D AOUATIC TOXICITY N/D \_\_\_\_\_\_ Section 13 -- DISPOSAL CONSIDERATIONS Waste Classification: Corrosive(D002) Disposal Method: Neutralization RCRA classified hazardous waste. Dispose of absorbed materials and liquid waste in accordance with all local, state and federal regulations. \_\_\_\_\_\_ Section 14 -- TRANSPORTATION INFORMATION DOT: UN1824, Sodium Hydroxide, Solution, Class 8, PG II, ERG#154 OCEAN (IMDG): UN1824, Sodium Hydroxide, Solution, Class 8, PG II, EMS-No: F-A, S-B AIR (IATA): UN1824, Sodium Hydroxide, Solution, Class 8, PG II, ERG#154 \_\_\_\_\_\_ Section 15 -- REGULATORY INFORMATION \_\_\_\_\_\_ REGULATORY DATA Ingredient Name \_\_\_\_\_\_ Sodium Hydroxide SARA 313 No TSCA Inventory 1000 lb. CERCLA RQ RCRA Code N/A Potassium Silicate SARA 313 TSCA Inventory Yes CERCLA RQ N/ARCRA Code N/A

WHMIS (CANADA): Class E

\_\_\_\_\_

Section 16 -- OTHER INFORMATION

\_\_\_\_\_\_

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001