

# SAFETY DATA SHEET

### 1. Identification

1. Identification				
Product identifier	HERCULES CLEAR, PURPLE, AND UNPURPLE PRIMER			
Other means of identification				
SDS number	7402E			
Synonyms	Part Numbers: Clear - 60453, 60458, 60460, 6 60425 Un-Purple - 60445, 60447	Part Numbers: Clear - 60453, 60458, 60460, 60465, 60470, Purple - 60403, 60413, 60415, 60420, 60425 Un-Purple - 60445, 60447		
Recommended use	Joining PVC Pipes			
Recommended restrictions	None known.			
Manufacturer/Importer/Supplier	/Distributor information			
Company Name Address	HCC Holdings, Inc. an Oatey Affiliate 4700 West 160th Street Cleveland, OH 44135			
Telephone	216-267-7100			
E-mail	info@oatey.com			
Transport Emergency	Chemtrec 1-800-424-9300 (Outside the US 1- 1-877-740-5015	703-527-3887)		
Emergency First Aid Contact person	MSDS Coordinator			
·				
2. Hazard(s) identification				
Physical hazards	Flammable liquids	Category 2		
Health hazards	Acute toxicity, oral	Category 4		
	Skin corrosion/irritation	Category 2		
	Serious eye damage/eye irritation	Category 2A		
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation		
	Specific target organ toxicity, single exposure	Category 3 narcotic effects		
	Aspiration hazard	Category 1		
OSHA defined hazards	Not classified.			
Label elements				
Signal word	Danger			
Hazard statement		swallowed. May be fatal if swallowed and enters s eye irritation. May cause respiratory irritation. May		
Precautionary statement				
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.			
Response	If swallowed: Immediately call a poison center contaminated clothing. Rinse skin with water/s keep comfortable for breathing. If in eyes: Rins	/doctor. If on skin (or hair): Take off immediately all shower. If inhaled: Remove person to fresh air and se cautiously with water for several minutes.		

keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Storage

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May form explosive peroxides. Contains a chemical classified by the US EPA as a suspected possible carcinogen.

### Supplemental information

Not applicable.

### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	CAS number	%
Acetone	67-64-1	30-60
Cyclohexanone	108-94-1	15-40
Furan, Tetrahydro-	109-99-9	10-30
Methyl ethyl ketone	78-93-3	10-30

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Most important symptoms/effects, acute and delayed	Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
• • • •	

General fire hazards

Highly flammable liquid and vapor. This product contains tetrahydrofuran that may form explosive organic peroxide when exposed to air or light or with age.

### 6. Accidental release measures

V. Accidental release mea	
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.
	Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

### Occupational exposure limits

109-99-9)

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Cyclohexanone (CAS 108-94-1)	PEL	200 mg/m3	
,		50 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	PEL	590 mg/m3	
,		200 ppm	
Methyl ethyl ketone (CAS 78-93-3)	PEL	590 mg/m3	
		200 ppm	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm	
-	TWA	20 ppm	
Furan, Tetrahydro- (CAS	STEL	100 ppm	

### **US. ACGIH Threshold Limit Values**

Components	Туре	Value	
	TWA	50 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	300 ppm	
	TWA	200 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Cyclohexanone (CAS 108-94-1)	TWA	100 mg/m3	
		25 ppm	
Furan, Tetrahydro- (CAS 109-99-9)	STEL	735 mg/m3	
		250 ppm	
	TWA	590 mg/m3	
		200 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	885 mg/m3	
		300 ppm	
	TWA	590 mg/m3	
		200 ppm	

#### **Biological limit values**

#### **ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*	
Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexan ediol, with hydrolysis	Urine	*	
	8 mg/l	Cyclohexanol, with hydrolysis	Urine	*	
Furan, Tetrahydro- (CAS 109-99-9)	2 mg/l	Tetrahydrofura n	Urine	*	
Methyl ethyl ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*	

\* - For sampling details, please see the source document.

#### **Exposure guidelines**

US - California OELs: Skir	designation	
Cyclohexanone (CAS 1	08-94-1)	Can be absorbed through the skin.
US - Minnesota Haz Subs:	Skin designation applies	
Cyclohexanone (CAS 1	08-94-1)	Skin designation applies.
US - Tennessee OELs: Sk	n designation	
Cyclohexanone (CAS 108-94-1)		Can be absorbed through the skin.
US ACGIH Threshold Limi	t Values: Skin designation	
Cyclohexanone (CAS 108-94-1)		Can be absorbed through the skin.
Furan, Tetrahydro- (CAS 109-99-9)		Can be absorbed through the skin.
US. NIOSH: Pocket Guide	to Chemical Hazards	
Cyclohexanone (CAS 1	08-94-1)	Can be absorbed through the skin.
Appropriate engineering controls Explosion-proof general and local exhaust ventilation. C changes per hour) should be used. Ventilation rates sho applicable use process enclosures, local exhaust ventil		e used. Ventilation rates should be matched

#### entilation (typically 10 air ed to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

#### Individual protection measures, such as personal protective equipment

Eye/face protection

Face shield is recommended. Wear safety glasses with side shields (or goggles).

Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

Appearance	Translucent.
Physical state	Liquid.
Form	Liquid.
Color	Clear. or Purple
Odor	Solvent.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	151 °F (66.11 °C)
Flash point	14.0 - 23.0 °F (-10.05.0 °C)
Evaporation rate	5.5 - 8
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	145 mm Hg @ 20 C
Vapor density	2.5
Relative density	0.82 - 0.86
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	< 100 cP
Other information	
Bulk density	7 lb/gal
VOC (Weight %)	505 g/I SQACMD Method 304
10 Stability and reactivity	

### 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Ammonia. Amines. Isocyanates. Caustics.

### 11. Toxicological information

#### Information on likely routes of exposure

Inhalation	May be fatal if swallowed and enters airways. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	May be fatal if swallowed and enters airways. Harmful if swallowed. Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

#### Information on toxicological effects

Acute toxicity

May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation.

Components	Species	Test Results	
Acetone (CAS 67-64-1)			
Acute			
Dermal			
LD50	Rabbit	20 ml/kg	
Inhalation			
LC50	Rat	50 mg/l, 8 Hours	
Oral			
LD50	Rat	5800 mg/kg	
Cyclohexanone (CAS 108-94-1	)		
Acute			
Dermal			
LD50	Rabbit	948 mg/kg	
Inhalation			
LC50	Rat	8000 ppm, 4 hours	
Oral			
LD50	Rat	1540 mg/kg	
* Estimates for product may	y be based on additional component data	a not shown.	
kin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye rritation	Causes serious eye irritation.		
Respiratory or skin sensitizat	ion		
Respiratory sensitization	Not available.		
Skin sensitization	This product is not expected to caus	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	In 2012 USEPA Integrated Risk Information System (IRIS) reviewed a two species inhalation lifetime study on THF conducted by NTP (1998). Male rats developed renal tumors and female mice developed liver tumors while neither the female rats nor the male mice showed similar results. Because the carcinogenic mechanisms could not be identified clearly in either species for either tumor, the EPA determined that the male rat and female mouse findings are relevant to the assessment of carcinogenic potential in humans. Therefore, the IRIS review concludes that these data in aggregate indicate that there is "suggestive evidence of carcinogenic potential" following exposure to THF by all routes of exposure.		

Cyclohexanone (CAS 108-94-1)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulate Not listed.	d Substances (29 CFR 1910.1001-1050)
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Narcotic effects. May cause drowsiness and dizziness. Respiratory tract irritation.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged inhalation may be harmful.

### 12. Ecological information

Ecoto	xicitv
LOOLO	Aloity.

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

	1 ,	<b>v</b> i i	00
Components		Species	Test Results
Acetone (CAS 67-64	-1)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	) > 100 mg/l, 96 hours
Cyclohexanone (CAS	S 108-94-1)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	) 481 - 578 mg/l, 96 hours

* Estimates for product may be	based on additional component data not shown.	
Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential	No data available.	
Partition coefficient n-octand	ol / water (log Kow)	
Acetone (CAS 67-64-1)	-0.24	
Cyclohexanone (CAS 108-94-	1) 0.81	
Furan, Tetrahydro- (CAS 109-9	99-9) 0.46	
Methyl ethyl ketone (CAS 78-9	3-3) 0.29	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	
13. Disposal consideration	S	
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/ational/international	

	regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

### 14. Transport information

DOT	
UN number	UN1993
UN proper shipping name	Flammable liquids, n.o.s. (Methyl ethyl ketone RQ = 25063 LBS, Acetone RQ = 12522 LBS)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II

Special precautions for user Special provisions Packaging exceptions Packaging non bulk Packaging bulk IATA	<ul> <li>Read safety instructions, SDS and emergency procedures before handling.</li> <li>IB2, T7, TP1, TP8, TP28</li> <li>150</li> <li>202</li> <li>242</li> </ul>
UN number	UN1993
UN proper shipping name	Flammable liquid, n.o.s. (Methyl ethyl ketone, Acetone)
Transport hazard class(es)	
Class	3
Subsidiary risk	
Packing group	II
Environmental hazards	No.
ERG Code	3H
Special precautions for user	· Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Methyl ethyl ketone, Acetone)
Transport hazard class(es)	
Class	3
Subsidiary risk	
Packing group	I
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	<ul> <li>Read safety instructions, SDS and emergency procedures before handling. Not available.</li> </ul>
15. Regulatory information	1
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)	LISTED
Cyclohexanone (CAS 108-94-1)	LISTED
Furan, Tetrahydro- (CAS 109-99-9)	LISTED
Methyl ethyl ketone (CAS 78-93-3)	LISTED

#### Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories Immediate Hazard - Yes

No

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

## SARA 313 (TRI reporting)

Not regulated.

Other federal regulations			
Clean Air Act (CAA) Section	n 112 Hazardous Air Polluta	nts (HAPs) List	
Not regulated. Clean Air Act (CAA) Sectior	n 112(r) Accidental Release	Prevention (40 CFR 68.130)	
Not regulated. Safe Drinking Water Act (SDWA)	Not regulated.		
		sential Chemicals (21 CFR 1310.02(b) a	and 1310.04(f)(2) and
Acetone (CAS 67-64 Methyl ethyl ketone	(CAS 78-93-3)	6532 6714 Exempt Chemical Mixtures (21 CFR 13	210 12(~))
		35 %WV	310.12(0))
Acetone (CAS 67-64 Methyl ethyl ketone DEA Exempt Chemical		35 %WV 35 %WV	
Acetone (CAS 67-64	,	6532 6714	
Methyl ethyl ketone US state regulations	(CAS 70-93-3)	6714	
US. Massachusetts RTK - S	ubstance List		
Acetone (CAS 67-64-1) Cyclohexanone (CAS 10 Furan, Tetrahydro- (CAS Methyl ethyl ketone (CAS	8-94-1) ; 109-99-9)		
US. New Jersey Worker and	d Community Right-to-Know	Act	
Acetone (CAS 67-64-1) Cyclohexanone (CAS 10 Furan, Tetrahydro- (CAS Methyl ethyl ketone (CAS	109-99-9)		
US. Pennsylvania Worker a		ow Law	
Acetone (CAS 67-64-1) Cyclohexanone (CAS 10 Furan, Tetrahydro- (CAS Methyl ethyl ketone (CAS US. Rhode Island RTK	109-99-9)		
Acetone (CAS 67-64-1) Cyclohexanone (CAS 10 Furan, Tetrahydro- (CAS Methyl ethyl ketone (CAS	5 109-99-9)		
		Act of 1986 (Proposition 65): This materi ductive toxins.	ial is not known to contain
International Inventories			
Country(s) or region	Inventory name		On inventory (yes/no)*
Australia	Australian Inventory of Che	mical Substances (AICS)	Yes
Canada	Domestic Substances List (		Yes
Canada	Non-Domestic Substances		No
China		ical Substances in China (IECSC)	Yes
Europe -	European Inventory of Exis Substances (EINECS)		Yes
Europe	-	hemical Substances (ELINCS)	No
Japan		ew Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (EC	<i>،</i> L)	Yes
New Zealand Philippines	New Zealand Inventory Philippine Inventory of Cher (PICCS)	micals and Chemical Substances	Yes Yes

#### Country(s) or region

#### Inventory name

#### United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

Issue date	17-December-2014
Revision date	-
Version #	01
HMIS® ratings	Health: 2 Flammability: 3 Physical hazard: 0
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. HCC Holdings Inc. an Oatey Affiliate cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.